## ADDITIONAL REQUIREMENTS FOR CATEGORY 3 PLUS SPECIAL REGULATIONS - EQUIPMENT REQUIREMENTS THIS SECTION IS TO BE COMPLETED AND INITIALED BY THE OWNER OR PERSON IN CHARGE AND A CEA / NEA RPAYC ACCREDITED AUDITOR

Date of Audit	Sail Number	Boat Name	Owner / PiC	<b>Equipment Auditor</b>

Category	SR	Item	Owner / PiC	Equipment Auditor	Comments
Cat 2	3.03	Hull Construction ISO 12215 Category A (Ocean).			
	3.25.1(c)	A Satellite Phone is <b>required</b> (changes SR 3.25.1) The satellite phone shall have coverage of the race area and be connected to the main power or have a spare battery.			
	2.27	to the main power or have a spare battery.			
	3.27	All boats shall have a fitted Barometer.			
4.09	4.09 (c)	An AIS Transponder is recommended. The Transponder			
		should be operational (transmitting and receiving), at regular			
		intervals (no less than every 5 minutes) for the duration of			
		the race. Not protestable by a boat, changes RRS60.1.			
	4.11	A second GPS which is handheld and water resistant with			
		spare battery(s) shall be provided.			
	4.18.2	The number of EPIRBs carried on board shall be not less than			
		the number of liferafts carried on the boat.			
	4.18.4	Additional EPIRBs required under SR4.18.2 may be packed in			
		each liferaft or stored in a dry, well-marked location near the			
		companionway.			
	4.19	Liferaft(s); with a capacity to accommodate at least the total			
		number of people aboard and complies with; SR4.19.1			
		Liferaft Construction, SR4.19.2 Minimum Liferaft Equipment,			
		SR4.19.3 Liferaft Packing and Stowage, SR4.19.4 Liferaft			
		Service and Inspection.			
	4.21 (b)	Lifebuoys: an additional lifebuoy with attached drogue, self-			
		igniting light, pole and flag is required			
	5.01	Lifejackets: A boat shall carry at least one spare lifejacket as			
		required in SR5.01.1.			
	5.02	Safety Harnesses and Safety Lines (Tethers): 5.02.2 In			
		addition to the requirement of 5.02.1(a), at least 30% of the			
		crew shall each be provided with either: (i) A safety line not			
		more than 1 m long or (ii) A mid-point manufacturer fitted			
		snap hook attachment on a 2 m safety line or (ii) Twin lines,			
		one not more than 1 m long and the other not more than 2 m			
		long.			
	5.05	Personal Locater Beacon: SR5.05.1 A GPS capable 406MHz			
		Personal Locator Beacon (PLB) registered with a national			
		registration authority shall be carried by or attached to each			
		member of the crew when on deck.			
DUTSTANDIN	IG ITEMS:	· · · · · · · · · · · · · · · · · · ·			

Attached this to your Cat 3 Audit Form and upload to your boats entry as one document.