AUSTRALIAN SAILING (AS) 2017-2021 SPECIAL REGULATIONS EQUIPMENT AUDIT FORM



CATEGORY	THE RESERVE AND PROPERTY.	DNOHULLS		ffshore Races of	long dista	nce near sho	reline	
DATE OF AUDIT	SAIL	NO:	BOAT	NAME:				
Audit form valid until 30 / 06 / (annual audit period July 1 to June 30). Expiry dates to be updated as required at bottom of current page to maintain compliance. Subject to spot checks Special Regulation (SR) 2.02.2.								
OWNER DETAILS			The State of the S					
OWNER(S) NAME(S):								
OWNER(S) AS NO(S):				OWNER(S) CLUB(S)				
BOAT DETAILS								
LH:				BOAT REGISTRATION	I NO:			
DISPL (tonnes):				MARITIME STICKER IS	SSUED	YES NO	N/A	
HULL COLOUR:				DISTINGUISHING MA	ARKS:			
DECK COLOUR:								
MAX CREW:				-				
RADIO & EPIRB REG	SISTRATION							
SR 3.25 MARINE RADIO		e Transceiver Licen	ce for HF	YES NO	Registered ca	II sign HF:	n X dec 700 Più et l'histille	
SR 4.18.1 EPIRB(s): Reg	istered YES	NO Number of	of units for b	oat:	Number to b			
SR 5.05.1 PLBs: Rec	gistered YES	NO Number of	of units for b	oat:	Number to b	oe hired:		
DECLARATION BY F	CATALOGUE AND	HARGE		STREET, STREET				
I have read and understan the person in charge), and organising authorities. I undefined in SRs 1.02.1, 1.02 Special Regulations 2017-	I SR 2.03.1 (Func nderstand that a .2, 1.02.3 and 2.0 2021, and ensur	tion of equipment). I n auditor does not li 03.1. I undertake tha	l understand tl mit or reduce t I will maintai	hat this audit is carried ou the complete and unlimit n in good working order a	t only as a guide ed responsibility	to persons in charge of the person in char	and race	
Signed by Person in C	Marine Day of the State of the	-i	w the felle	Date:			• • •	
OUTSTANDING ITE Outstanding Item	ivis - The eq	uipment iistea i	n the follo	Re-Inspected by	пріете ехсер	AS Auditor No.	Date	
				The Inspected by		713 Madret 110.	Date	
¥								
EQUIPMENT AUDIT I have checked the above			SR 2 02 2 as su	immarised in the following	a list, and the ite	ms listed were compl	iant as per	
the AS Special Regulation	s at the time and	date of this audit. (Form not to b	e signed until outstanding	items detailed a	bove have been rect	rified).	
Audited by AS NEA: (print name)				Signed by AS NEA:				
AS Number:				Date:				
EARLIEST EXPIRY DATES – indicate 'hire' or not applicable 'n/a' if relevant								
ITEM	EARLIEST EXPIRY	UPDATED EARLIEST EXPIRY	AUDITOR	ITEM	EARLIEST EXPIRY	UPDATED EARLIEST EXPIRY	AUDITOR	
Radio certificate Fire ext (12 mth.)				Flares parachute				
EPIRB(s)				Flares red nand				
Liferaft(s)				Flares orange hand				
Inflatable lifebuoy(s)				Lifejackets				
Inflatable danbuoy(s)				PLBs				
Trysail or 50% reefing (
		ccent self-servicing o	of fire extinguis	shers and lifejackets. Chec	ck with the club f	or specific requireme	ents	

AUSTRALIAN SAILING (AS) 2017-2021 SPECIAL REGULATIONS EQUIPMENT AUDIT FORM



CATEGORY 2 MONOHULLS For Offshore Races of long distance near shoreline

DATE OF AUDIT

___/___/____ BOAT NAME:

This section to be completed and **ticked or initialled** by person in charge (P) and auditor(A). If item not applicable, mark 'n/a' or dash '-

Reg 2.03.1	Structural/Fived Dack Itams	P
	Structural/Fixed Deck Items	
2.03.1	Equipment functions & adequate for intended use Ballast & heavy equipment secured	
21400000 (2000)	(a) 2 exits, 1 forward of mast	
3.06.1	(Refer to regulation for minimum clearance)	
	(a) No hatches forward of maximum beam open	
2.07.4	inwards except if size < 0.071 m ²	
3.07.1	(b) Non-conforming hatches labelled 'Not to be	
	opened at sea'	
	(a)(i) Hatches above water when heeled 90°	
	(a)(ii) 4 non-conforming hatches permitted; 2 per	
3.07.2	side, size < 0.071 m ²	
0.07.2	(a)(ii) Non-conforming hatches kept shut while racing	
	(b) Hatches capable of being immediately shut;	
0.07.0	permanently attached lid	
3.07.3	Blocking device for low sill companionway	
	(a) Companionway hatch securing arrangement	
	(i) Operable from above and below	
3.07.4	(ii) Functions independently of blocking devices	
3.07.4	(b) Blocking devices to be	
	(i) Capable of being retained with hatch open or shut (ii) Secured to boat (e.g. by lanyard)	
3.08.1	(iii) Permit exit in event of inversion Cockpit strong, self-draining, & watertight (3.08.2)	
3.08.3	Bilge pump outlet not connected to cockpit drain	
0.00.0	Number of cockpit drains required: <8.5 m: 2 x 25 mm	
3.08.7	Age/Series Date pre 07/77 & >8.5 m; 2 x 25 mm	
0.00.7	Age/ Series Date post 07/77 & >8.5 m; 4 x 20 mm	
3.12.2	Lifelines taut (50 N force applied; ≤ 50 mm deflection)	
011212	Bow pulpits shall be either:	
	(a)(i) Closed and forward of forestay; OR	
	(a)(ii) Open with the forward gap ≤ 360 mm; OR	
	(a)(iii) Open with the gap to any boat part ≤ 360 mm	
	(b) & (d) Bow and stern pulpit top rails same height	
	as upper lifelines	
	(c) Lifelines, stanchions, pulpits effectively	
3.12.3	continuous deck barrier	
3.12.3	(f) Pulpits & stanchions permanently installed	
	(g) Pulpit & stanchion bases inboard ≤ 5% of max	
	beam or 150 mm	
	(h) Stanchion bases not outboard	
	(j) Lifelines attached to stanchion inside &	
	overlapping pulpit with gap ≤ 150 mm permitted	
	(k) Stanchions straight, vertical; first 50 mm ≤ 10 mm	
	displ. and angle ≤ 10 deg. from 50 mm above deck.	
3.12.5		
J. 12.U	Lifeline height, spacing, number comply with table	
J. 12.U	(a) Lifelines uncoated stainless steel wire	
	(a) Lifelines uncoated stainless steel wire(d) Gap secured by lanyard ≤ 100 mm;	
3.12.6	(a) Lifelines uncoated stainless steel wire(d) Gap secured by lanyard ≤ 100 mm;Lanyard replaced annually	
	 (a) Lifelines uncoated stainless steel wire (d) Gap secured by lanyard ≤ 100 mm; Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire 	
3.12.6	 (a) Lifelines uncoated stainless steel wire (d) Gap secured by lanyard ≤ 100 mm; Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Toe rail min height 25 mm (age date from 01/81); 	
	 (a) Lifelines uncoated stainless steel wire (d) Gap secured by lanyard ≤ 100 mm; Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Toe rail min height 25 mm (age date from 01/81); Toe rail min height 20 mm (age date before 01/81) 	
3.12.6	 (a) Lifelines uncoated stainless steel wire (d) Gap secured by lanyard ≤ 100 mm; Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Toe rail min height 25 mm (age date from 01/81); Toe rail min height 20 mm (age date before 01/81) 2 manual bilge pumps; 1 above, 1 below operable 	
3.12.6	 (a) Lifelines uncoated stainless steel wire (d) Gap secured by lanyard ≤ 100 mm; Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Toe rail min height 25 mm (age date from 01/81); Toe rail min height 20 mm (age date before 01/81) 2 manual bilge pumps; 1 above, 1 below operable with boat/seats shut; permanent discharge pipes 	
3.12.6	 (a) Lifelines uncoated stainless steel wire (d) Gap secured by lanyard ≤ 100 mm; Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Toe rail min height 25 mm (age date from 01/81); Toe rail min height 20 mm (age date before 01/81) 2 manual bilge pumps; 1 above, 1 below operable with boat/seats shut; permanent discharge pipes Bilge pump not to discharge into closed cockpit 	
3.12.6 3.14.1 3.20.1	(a) Lifelines uncoated stainless steel wire (d) Gap secured by lanyard ≤ 100 mm; Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Toe rail min height 25 mm (age date from 01/81); Toe rail min height 20 mm (age date before 01/81) 2 manual bilge pumps; 1 above, 1 below operable with boat/seats shut; permanent discharge pipes Bilge pump not to discharge into closed cockpit Bilge pump not connected to cockpit drains	
3.12.6 3.14.1 3.20.1	(a) Lifelines uncoated stainless steel wire (d) Gap secured by lanyard ≤ 100 mm; Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Toe rail min height 25 mm (age date from 01/81); Toe rail min height 20 mm (age date before 01/81) 2 manual bilge pumps; 1 above, 1 below operable with boat/seats shut; permanent discharge pipes Bilge pump not to discharge into closed cockpit Bilge pump not connected to cockpit drains a) Bilge pump minimum suction bore 25 mm	
3.12.6 3.14.1 3.20.1 3.20.6	(a) Lifelines uncoated stainless steel wire (d) Gap secured by lanyard ≤ 100 mm; Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Toe rail min height 25 mm (age date from 01/81); Toe rail min height 20 mm (age date before 01/81) 2 manual bilge pumps; 1 above, 1 below operable with boat/seats shut; permanent discharge pipes Bilge pump not to discharge into closed cockpit Bilge pump not connected to cockpit drains a) Bilge pump minimum suction bore 25 mm b) Bilge pump & strum boxes accessible	
3.12.6 3.14.1 3.20.1 3.20.6	(a) Lifelines uncoated stainless steel wire (d) Gap secured by lanyard ≤ 100 mm; Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Toe rail min height 25 mm (age date from 01/81); Toe rail min height 20 mm (age date before 01/81) 2 manual bilge pumps; 1 above, 1 below operable with boat/seats shut; permanent discharge pipes Bilge pump not to discharge into closed cockpit Bilge pump not connected to cockpit drains a) Bilge pump minimum suction bore 25 mm b) Bilge pump & strum boxes accessible Pump handle each with lanyard or catch unless	
3.12.6 3.14.1 3.20.1 3.20.6 3.20.7	(a) Lifelines uncoated stainless steel wire (d) Gap secured by lanyard ≤ 100 mm; Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Toe rail min height 25 mm (age date from 01/81); Toe rail min height 20 mm (age date before 01/81) 2 manual bilge pumps; 1 above, 1 below operable with boat/seats shut; permanent discharge pipes Bilge pump not to discharge into closed cockpit Bilge pump not connected to cockpit drains a) Bilge pump minimum suction bore 25 mm b) Bilge pump & strum boxes accessible Pump handle each with lanyard or catch unless permanently fitted	
3.12.6 3.14.1 3.20.1 3.20.6 3.20.7	(a) Lifelines uncoated stainless steel wire (d) Gap secured by lanyard ≤ 100 mm; Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Toe rail min height 25 mm (age date from 01/81); Toe rail min height 20 mm (age date before 01/81) 2 manual bilge pumps; 1 above, 1 below operable with boat/seats shut; permanent discharge pipes Bilge pump not to discharge into closed cockpit Bilge pump not connected to cockpit drains a) Bilge pump minimum suction bore 25 mm b) Bilge pump & strum boxes accessible Pump handle each with lanyard or catch unless permanently fitted Marine magnetic compass permanently installed,	
3.12.6 3.14.1 3.20.1 3.20.6 3.20.7 3.20.8 3.21.1	(a) Lifelines uncoated stainless steel wire (d) Gap secured by lanyard ≤ 100 mm; Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Toe rail min height 25 mm (age date from 01/81); Toe rail min height 20 mm (age date before 01/81) 2 manual bilge pumps; 1 above, 1 below operable with boat/seats shut; permanent discharge pipes Bilge pump not to discharge into closed cockpit Bilge pump not connected to cockpit drains a) Bilge pump minimum suction bore 25 mm b) Bilge pump & strum boxes accessible Pump handle each with lanyard or catch unless permanently fitted Marine magnetic compass permanently installed, non-electric	
3.12.6 3.14.1 3.20.1 3.20.6 3.20.7 3.20.8 3.21.1 3.21.2	(a) Lifelines uncoated stainless steel wire (d) Gap secured by lanyard ≤ 100 mm; Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Toe rail min height 25 mm (age date from 01/81); Toe rail min height 20 mm (age date before 01/81) 2 manual bilge pumps; 1 above, 1 below operable with boat/seats shut; permanent discharge pipes Bilge pump not to discharge into closed cockpit Bilge pump not connected to cockpit drains a) Bilge pump minimum suction bore 25 mm b) Bilge pump & strum boxes accessible Pump handle each with lanyard or catch unless permanently fitted Marine magnetic compass permanently installed, non-electric Spare magnetic compass non electric (portable ok)	
3.12.6 3.14.1 3.20.1 3.20.6 3.20.7 3.20.8 3.21.1 3.21.2 3.23	(a) Lifelines uncoated stainless steel wire (d) Gap secured by lanyard ≤ 100 mm; Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Toe rail min height 25 mm (age date from 01/81); Toe rail min height 20 mm (age date before 01/81) 2 manual bilge pumps; 1 above, 1 below operable with boat/seats shut; permanent discharge pipes Bilge pump not to discharge into closed cockpit Bilge pump not connected to cockpit drains a) Bilge pump minimum suction bore 25 mm b) Bilge pump & strum boxes accessible Pump handle each with lanyard or catch unless permanently fitted Marine magnetic compass permanently installed, non-electric Spare magnetic compass non electric (portable ok) Navigation lights carried complying with IRPCAS	
3.12.6 3.14.1 3.20.1 3.20.6 3.20.7 3.20.8 3.21.1 3.21.2	(a) Lifelines uncoated stainless steel wire (d) Gap secured by lanyard ≤ 100 mm; Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Toe rail min height 25 mm (age date from 01/81); Toe rail min height 20 mm (age date before 01/81) 2 manual bilge pumps; 1 above, 1 below operable with boat/seats shut; permanent discharge pipes Bilge pump not to discharge into closed cockpit Bilge pump minimum suction bore 25 mm b) Bilge pump & strum boxes accessible Pump handle each with lanyard or catch unless permanently fitted Marine magnetic compass permanently installed, non-electric Spare magnetic compass non electric (portable ok) Navigation lights carried complying with IRPCAS (b) Masthead VHF antenna	
3.12.6 3.14.1 3.20.1 3.20.6 3.20.7 3.20.8 3.21.1 3.21.2 3.23	(a) Lifelines uncoated stainless steel wire (d) Gap secured by lanyard ≤ 100 mm; Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Toe rail min height 25 mm (age date from 01/81); Toe rail min height 20 mm (age date before 01/81) 2 manual bilge pumps; 1 above, 1 below operable with boat/seats shut; permanent discharge pipes Bilge pump not to discharge into closed cockpit Bilge pump not connected to cockpit drains a) Bilge pump minimum suction bore 25 mm b) Bilge pump & strum boxes accessible Pump handle each with lanyard or catch unless permanently fitted Marine magnetic compass permanently installed, non-electric Spare magnetic compass non electric (portable ok) Navigation lights carried complying with IRPCAS (b) Masthead VHF antenna Hull Identification, min 50 mm; name & state rego;	
3.12.6 3.14.1 3.20.1 3.20.6 3.20.7 3.20.8 3.21.1 3.21.2 3.23 3.25.4 3.28.1	(a) Lifelines uncoated stainless steel wire (d) Gap secured by lanyard ≤ 100 mm; Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Toe rail min height 25 mm (age date from 01/81); Toe rail min height 20 mm (age date before 01/81) 2 manual bilge pumps; 1 above, 1 below operable with boat/seats shut; permanent discharge pipes Bilge pump not to discharge into closed cockpit Bilge pump minimum suction bore 25 mm b) Bilge pump & strum boxes accessible Pump handle each with lanyard or catch unless permanently fitted Marine magnetic compass permanently installed, non-electric Spare magnetic compass non electric (portable ok) Navigation lights carried complying with IRPCAS (b) Masthead VHF antenna Hull Identification, min 50 mm; name & state rego; OR name, sail number & club	
3.12.6 3.14.1 3.20.1 3.20.6 3.20.7 3.20.8 3.21.1 3.21.2 3.23 3.25.4	(a) Lifelines uncoated stainless steel wire (d) Gap secured by lanyard ≤ 100 mm; Lanyard replaced annually (e) Total lifeline system ≥ strength of required wire Toe rail min height 25 mm (age date from 01/81); Toe rail min height 20 mm (age date before 01/81) 2 manual bilge pumps; 1 above, 1 below operable with boat/seats shut; permanent discharge pipes Bilge pump not to discharge into closed cockpit Bilge pump not connected to cockpit drains a) Bilge pump minimum suction bore 25 mm b) Bilge pump & strum boxes accessible Pump handle each with lanyard or catch unless permanently fitted Marine magnetic compass permanently installed, non-electric Spare magnetic compass non electric (portable ok) Navigation lights carried complying with IRPCAS (b) Masthead VHF antenna Hull Identification, min 50 mm; name & state rego;	

arge (P) ai	nd auditor(A). If item not applicable, mark 'n/a' or c	lash	'-'
	(a) Clipping points through bolted or welded deck		
4.03.2	plates or other suitable strong points	-	
4.03.2	(b) Positioned to clip/unclip from below and move between cockpit and deck		
9	(c) Clipping points for 2/3 crew		
Reg	Structural/Fixed Items Below	Р	Α
	(a) Seacocks permanently installed		
3.09.1	(b) Plugs for each opening attached or stowed nearby		
3.11	Keel stepped mast; heel securely fastened		
3.15.1	Toilet, securely installed (N.B. includes plumbing)		
3.16.1	Bunks, securely fastened, sufficient 50% of crew		
3.16.2	Lee cloths/restraints for fixed bunks		
3.17.1	Cooking stove/heating appliance safe use in seaway		
3.17.2	e.g. Gimballed with accessible shutoff		
3.17.3	Gas or methylated spirits only fuels for cooking		
3.17.4	(a) "REMEMBER Turn Off Gas At Bottle" sign		
	(b) Gas detection for permanent pilot light		
3.17.5	Disposable gas canisters ≤ 225 grams		
3.17.6	Gas bottle, spare canisters in separate compartment		
2 17 7	ventilated overboard	-	
3.17.7	Galley - suitable facilities		
3.18.1	2 permanently installed water tanks or divided compartments with pump		
3.19.1	Handholds below decks	\vdash	
	Inboard engine, tank(s), fuel & exhaust system;		
3.24.1	permanently installed		
3.24.6	Separate starter battery if electric starter		
3.24.7	Separate generators, if carried, securely covered and		
	permanently installed		
3.24.8	Fuel tank shut off valve/cock if fuel can escape or siphon		
	(a) Petrol tanks – see regulation	\vdash	
3.24.9	(b) Diesel tanks metal or other certified material		
15,000 10.50	(c) Fuel lines comply		
	(a)(i)(ii) & (c) Permanently installed HF transceiver		
3.25.1	(new installations DSC capable)		
3.23.1	(b)(i)(iii) & (c) Permanently installed VHF transceiver		
	(new installations DSC capable)		
3.26	Batteries sealed type; electrolyte cannot escape		
3.27	Barometer fitted		
4.09	(b) AIS transponder recommended		
4.11	GPS permanently installed, with MOB function		
4.12	Depth Sounder		
4.13.1	Log (other than GPS)		
CONTRACTOR DESCRIPTION	THE PARTY OF THE P		
Reg	Portable Equipment	P	Α
3.18.4	Emergency water 1 litre per crew additional		
3.20.9	2 x 8 litre buckets, stout construction with lanyard		
3.23.4	Reserve navigation lights, independent of main		
2.02.5	power	-	
3.23.5	Spare bulbs except for multiple LED array Handheld VHF transceiver; waterproof		
	(a) Emergency HF antenna		
3.25.5	(a) Emergency VHF antenna		
4.01.2	Portable sail number on separate cloth with lanyards		
4.03.1	(b) Jackstays (1 port, 1 starboard); strength &		
	materials as per regulation		
4.04.1	2 x fire extinguishers 10BE dry powder min or equiv.		
4.04.4	Fire blanket (for cooking device with open flame)		
	(a) Anchors & ground tackle as per Table 1		
1.05.1	(b) Anchor & warp sizes Table 2 or Table 3		
4.05.1	Anchor 1 Typekg/size Anchor 2 Typekg/size		
	(c) Primary anchor assembled, attached to tackle		
	(i) Watertight spotlight; spare batteries & bulbs if		
4.06.1	replaceable		
4.00.1	(ii) 2 x flashlight floating type; spare batteries & bulbs		
	if replaceable		

AUSTRALIAN SAILING (AS) 2017-2021 SPECIAL REGULATIONS EQUIPMENT AUDIT FORM



CATEGORY 2 MONOHULLS For Offshore Races of long distance near shoreline

DATE OF AUDIT SAIL NO:

BOAT NAME:

4.07.2	First aid manual					
4.07.4	First aid kit, waterproof container; contents listed;					
4.07.9	alternative brands permitted					
4.07.9	First aid contents as per list at end of this form					
4.08	Foghorn					
4.10.1	Charts (not solely electronic), plotting equipment					
4.10.2	Collision Regulations; electronic or hard copy					
4.10.3	Current AS "Racing Rules of Sailing" and "Special					
4.11.2	Regulations Part 1"; electronic or hard copy	-				
4.11.2	Handheld GPS, water resistant, spare batteries Emergency tiller if not tiller steered	+				
4.14.1	Alternative steering method for rudder loss	+-				
4.15.1	Tools, spares parts, effective way to cut rigging	-				
4.15.1	Bosun's chair or climbing harness	+				
4.15.3	Sharp knife sheathed, restrained in or near cockpit	+				
4.16.1		+				
4.16.1	Name on all buoyant equipment & items	+-+				
4.10.2	Personal lifejacket marked to identify owner					
	Retroreflective tape on lifebuoys, lifeslings, liferafts 406MHz EPIRB; GPS capable	-				
4.18.1	Number of EPIRBs ≥ number of liferafts	-				
4.18.2	Number of EPIRBs 2 number of liferafts Number of EPIRBs					
	(c) Regularly tested	+-				
4.18.3	(d) Registered with relevant authority	+				
4.10.0	Crew trained in use	650				
	Liferaft compliant type as per 4.19.1 and 4.19.2	1				
4.19.1	No. of liferafts Total crew capacity					
	Liferaft stowage					
	(a)(i) Rigid container; on working deck/cockpit; OR					
	(a)(ii) Rigid container or valise stowed in dedicated					
4.19.3	locker opening to cockpit/working deck/transom; OR					
4.10.0	(b) If boat launch before 06/2001, valise ≤40kgs					
	stowed below near companionway permitted					
	(d) Painter should be made fast to strong point					
	(e) Life raft launch time 15 seconds (a) Lifebuoy; self-igniting light, drogue; in reach; OR					
	Lifesling, self-igniting light; in reach					
	(b) Additional lifebuoy, in reach of helmsman	+				
4.21.1	(b)(i) Whistle, drogue, self-igniting light					
	(b)(ii) Pole and flag floating 1.8 metres above water,					
	attached to lifebuoy with 3 metres of line					
4.21.2	1 x lifebuoy to be of permanent buoyancy	+				
4.21.4	Lifebuoys, lifeslings fitted with retroreflective material					
4.21.5	Lifebuoys, lifeslings safety colour					
	Waterproof container for flares					
	4 x red parachute flares					
4.22.1	4 x red hand flares					
	2 x white hand flares					
	4 x orange smoke flares					
4.23.1	Heaving line minimum 15 m	\top				
	(a) Storm jib; area compliant					
4044	(b) Storm trysail; area compliant OR mainsail reefing					
4.24.1	50% of luff					
	(c) Heavy weather jib; area compliant					
	(a) Highly-visible colour; OR					
	if purchased before 07/2005, patches 20% of area					
	(b) Sheeting positions for storm, heavy weather sail					
4.24.2	(c) Storm & heavy weather jib means of attachment					
	to stay independent of any luff-groove device	+				
	(d) Sail numbers both sides trysail					
	(e) Storm trysail to set with in-mast furling mainsail					
4.24.3	(a) Aromatic polyamides, carbon fibre & similar not					
	used for storm jib, trysail	1				
4.26	Retrieval method of crew from water					
	1151					
4.27	V Distress sheet or International signal	1				
4.27 4.28.1	V Distress sheet or International signal Stowage chart, displayed	+				

	(a) Lifejacket ≥ 150N (not "Mae West"), in service;					
	1 per crew, plus minimum 1 spare (f)(I)					
	Number (1 per crew)					
	Number (minimum 1 spare)					
5.01.1	Total on board:					
	(See regulation for compliance standards)					
	(d) Each lifejacket retro tape, whistle, crotch strap/s					
	(f)(ii) If inflatable, min 1 spare cylinder & (if					
	appropriate) spare auto rearming kit					
	Safety harness, line with snap hook each end (≤2 m);					
5.02.1	1 per crew Number					
	(See regulation for compliance standards)	-				
	For 30% of crew					
5.02.2	(i) Tethers 1m long (in addition to 5.02.1) No					
0.02.2	OR included in 5.02.1 as follows:					
	(ii) 2 m with midpoint clip OR No					
	(iii) Twin lines, one ≤ 1 m & second ≤ 2 m No					
5.03	Personal light (strobe or SOLAS LSA 2.2.3);					
5.03	1 per crew Number					
5.05.1	406 MHz Personal Locator Beacon (PLB) with GPS;					
5.05.1	1 per crew Number					
	(a) PLB Within battery life					
5.05.2	(b) Regularly tested					
	(c) Registered with relevant authority					
5.05.3	Crew to be trained in use of PLBs	1900				

4.07.9 First Aid Kit Contents List – within expiry date							
NON-PRESCRIPTION	Р	Α	NON-PRESCRIPTION	Р	Α		
Paracetamol 500 mg (e.g.			Anti-diarrhoea treatment				
Panadol) or Ibuprofen			(e.g. Imodium) x 1				
200 mg (e.g. Nurofen) x 40			Electrolyte 4.9 g - pkt of 10				
Soluble Aspirin (e.g.			(e.g. Gastrolyte) x 1				
Disprin) x 20			Seasickness tablets (e.g.				
Nitrolingual Spray (e.g.			Avomine, Travacalm) x 10				
Anginine) x 1			Scissors, stainless steel x 1				
Butterfly or Steristrips			Thermometer, clinical x 1				
(strips of 5) x 10			Forceps, splinter x 1				
Disposable gloves x 20			Syringes/needles x 5		,		
Crepe bandages 75 mm x			Alcohol swabs x 10				
1.5 m x 2			Splints for arms & legs				
Crepe bandages 100 mm			CPR mask or 6 face shields				
x 1.5 m x 2			PRESCRIPTION	Р	Α		
Triangular bandage x 2			PRESCRIPTION	P	A		
High absorbency non-			Codeine 8 mg +				
adherent dressing (e.g.			Paracetamol 500 mg				
Exu-dry) x 10			(e.g. Panadeine) x 40				
Low absorbency non-			Codeine 30 mg +				
adherent dressing/plain			Paracetamol 500 mg (e.g.				
gauze (e.g. Melolin) x 10			Panadeine Forte) x 20				
Bandaids or equivalent roll			Oxycodone 5 mg (e.g.				
of bandaid x 20			Endone) x 20 or				
Sports/Strapping tape 50			Oxycodone suppositories 30				
mm x 2.5 m (e.g.			mg (e.g. Proladone) x 10				
Leukoplast) x 1			Chloramphenicol eye				
Antiseptic skin solution			ointment 1% 4 mg x 1				
15 ml (e.g. Betadine) x 1			Cephalexin 500 mg tabs				
Antiseptic cream e.g.			(e.g. Keflex) x 20				
Medicreme x 1			Antihistamine 25 mg tabs				
Normal saline 250 ml x 1			(e.g. Phenergan) x 25				
Sterile eye patches x 5			Adrenaline ampoules				
Clotrimazole cream (e.g.			1:1000 x 5				
Lamisil, Daktarin) x 1			IF NOTICE OF RACE	P	Α		
Hydrogel wound dressing			***Morphine				
100 g (e.g. Solosite,			***Naloxone hydrochloride				
Duoderm, Purilon) x 1			***Additional 15 syringes				
Sunscreen 30+ 250 ml x 1							

END OF FORM

SPECIAL REGULATIONS - EQUIPMENT REQUIREMENTS THIS SECTION IS TO BE COMPLETED AND INITIALED BY THE OWNER OR PERSON IN CHARGE AND A CEA / NEA RPAYC ACCREDITED AUDITOR

Date of Audit	Sail Number	Boat Name	Owner / PiC	Equipment Auditor

Audits for RPAYC Members will take place at a pre-arranged time through the Sailing Office and bookings are essential. Audits may be conducted on Wednesday and or Saturday mornings, subject to the availability of a CEA / NEA accredited Equipment Auditor.

All gear shall be laid out for inspection. Where equipment is not adequately laid out, the Equipment Auditor may refuse to continue the audit. The boat's 'Owner' or 'Person in Charge' and one crew member shall be in attendance during the audit.

Where a boat has 'outstanding items' still required as part of its audit, it shall be ineligible to race. Outstanding items shall be presented with audit form for sign off to the original conducting CEA / NEA accredited Equipment Auditor or the RPAYC Sailing Office.

Under Australian Sailing Special Regulations 2.02, every boat may be subject to a 'spot check' equipment audit. A boat whose equipment is found to be non-complying or whose 'Owner' or 'Person in Charge' acts unreasonably in preventing a 'spot check', may be subject to protest by the Race Committee.

Each boat must comply with the nominated race category requirements and carry the specified equipment on board during the race.

A boat that competes without ensuring the Sailing Office has received and approved their valid AS SR compliance audit form will be scored by the Race Committee as DSQ without a hearing (this amends RRS 63.1, and Appendix A5).

It is the responsibility of the Owner and/or Person-in-Charge (PiC) to ensure that equipment is maintained, stowed and ensure that the boat continues to comply in every respect with the category the boat is competing in. The Owner and/or the Person-in-Charge should remain familiar with the current AS Special Regulations and ensure that all equipment remains on the boat, is kept in good order and that equipment is replaced or repaired as necessary and that the crew know where it is kept and how it is to be used.

Where a change of boat ownership occurs any existing AS SR compliance audit form approved prior to the change of ownership is void. The boat shall be re-audited in the case of an ownership change and meet the requirements of NoR 4.1 and 4.2 to be eligible to compete in RPAYC race events.

ADDITIONAL EQUIPMENT REQUIRED

by The RPAYC Sailing Handbook Notice of Race and General Sailing Instructions

Category	SR / NoR	Item	Owner / PiC	Equipment Auditor	Comments
All	4.07.9	1 x thermal aid			
Categories		(space blanket)			
7	5.01.1	Lifejackets in service complying with			
	amends	AS4758-2015 (minimum Level 100) or			
	(i)	AS1512-1996 Type 1 or Equivalent or			*****
		more stringent overseas standard			
All	NoR	Emergency Contact Sticker displayed			
Categories	***************************************				
7	NoR	VHF Transceiver (Fixed or handheld)			
7	NoR	Navigation Lights (Fixed or removable)			
7	NoR	V-Sheet			
7	NoR	Magnetic Compass			
7	NoR	Appropriate chart or map of sailing area			
7	NoR	Flares: 2 x Orange / 2 x Red			
		Earliest Exp			
7	NoR	Drinking Water 2L per person			
7	NoR	Sound signaling device			
		(e.g. Fog Horn)			
4	NoR	EPIRB (registered with AMSA)			Documentation required
4	NoR	Jackstays (recommended)			
4	NoR	Crotch straps (recommended)			
OUTSTANDING	ITEMS:			, ,,,,	
	ı				
	ļ				